

BOUBYAN INTERNATIONAL COMPANY

No:507,5th Floor,

Al-Rihab Complex, Tunis Street,

Hawally, State of Kuwait

Ph. + 91 99424 66663 / + 974 77061 797

Email: ibd@boubyaninternational.com

Website:www.boubyaninternational.com

PRODUCT: BLEACHING POWDER SPECIFICATIONS

- 1. The material shall be white to slightly yellowish –white in appreance and shall be freefrom hard lumps and any visible impurities. It shall be dry and free flowing.
- 2. The material shall evolve chlorine copiously on the additional of 2 mol/1 solution of Hydrochloric Acid. When the material is shaken with the water and filtered, the filtrateshall yield the two reactions prescribed in Appendix B of SLS 759: 1986, which is authentic for Calcium Salts and Chlorides.

REQUIREMENT FOR CHLORINATED LIME & CALCIUM HYDROCHLORITE.

Characteristics	Chlorinated Grade 1
Loss of available chlorine on heating	34-35.0%
Loss of available chlorine on	6.6%, max

heating	
on the basis of initial available chlorine mass Moisture, mass	0.3% max
Particle size (a) Particle passing through	
1.70 mm sieve, mass	99.5%, min
Bulk density (g/ml.)	0.8 min

Packing:

- 1. 25 Kgs HDPE Bag
- 2.The material shall be packed in air- tight, galvanized steel drums (50-Kgs.) made out of guage galvanized sheet with suitable inner linings or other similar container but minimum order should be 16 attain time.